Catalogue
FOOD SERVICE
Chapter
REFRIGERATION

Specific model
MFIM-400S A 230V 1N 50Hz

19031794 29/03/2021

DENOMINATION:

Modular solid ice-cube maker (S 20gr) with air condensation system.

DESCRIPTION :

Crystal clear and compact Gourmet ice cubes take a long time to melt while chilling your drink. Large compact Gourmet ice cubes are highly demanded by professionals and consumers. They are ideal for alcohol free drinks and spirits.
These ice cubes melt very slowly and consumers can enjoy their drinks at their ease.

General characteristics:
- Made of AISI-304 high quality steel and built-in door.
- Hazard-free stainless steel inward opening door.
- Front ventilation system.
- Outside ON/OFF switch.
- Flexible injectors for improved performance with heavily scaled water supply.
- Made by top performance electromechanical equipment. A limescale filter is recommended for water with high limescale content.
- Kg/24h production capacity at 20 ºC room temperature and 15 ºC water supply.
- ¾" water inlet.
- Single phase 230V/50Hz connection (230V/60Hz optional connection).
- Highly efficient equipment, low power consumption.
- Flexible injectors for improved performance with heavily scaled water supply.
- Stackable units by means of specific stacking kit.
- Troubleshooting acoustic alarm (only 400 model).
- Cleaning function for regular maintenance (only 400 model).
- Kg/24h production capacity at 20 ºC room temperature and 15 ºC water supply.
- R404a coolant.
- ¾" water inlet.
- Single phase 230V/50Hz connection (220V/60Hz optional connection).
- Except for MFIM-400 models 380V/3N/50Hz (220V/60HZ optional).

POSSIBLE ACCESSORIES :

- ACCESSORIES FOR ICE MAKERS

DIMENSIONS



X Width	1321 mm	X Gross width	1410 mm
Y Depth	638 mm	Y Gross depth	740 mm
Z Height	978 mm	Z Gross height	1115 mm
Net Weight	75,0 kg	Gross Weight	85,0 kg
Net volume	0,824 m3	Gross volume	1,163 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	3,300 kW
Voltage	230V - 1N
Electric frequency	50Hz

WATER TECHNICAL SPECIFICATIONS

Water max consumption	4,40 L/h

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 4 A
Water inlet diameter	3/4"
Drain 1 diameter	24X22

OTHERS

Kg/24 hours production	380,00 kg
Condensation system	Air
Cube size	20,00 g