



Catalogue
FOOD SERVICE

FMV

Chapter
REFRIGERATION

Zone:

Specific Model
UP-451 SS 230V 1N 50HZ

Item:

19089730

07/11/2025

The photo may show the standard model and not the configured one

DENOMINATION:

Professional refrigerated cabinet (stainless steel exterior) with 3+1 shelves.

DESCRIPTION :

- Exterior made of stainless steel.
- Inner body made of ABS food grade material.
- Rounded edges and corners on the inside for easy cleaning.
- Door with built-in handle.
- Reversible door.
- Fitted with key lock as standard.
- Digital thermometer with temperature control.
- Working voltage: 230 V - 50 Hz.

- Interior constructed with white coated galvanized steel.
- Doors with ergonomic, full-length, robust, perfectly integrated handle that ensures practical opening and avoids dust and dirt collection.
- Internally designed static cooling system. Interior shelves built-in epoxy coated copper pipes, acts as an evaporator to cool down the products.
- Ice defrosting process needs to be done manually.
- 400 and 600 models with 7 levels of grills and 235mm distance among them.
- 200 models with 3 levels and 200mm distance among them.

POSSIBLE OPTIONS :

- 60 Hz
- UK plug
- Wheels Kit (Factory Assembly)

SUPPLIED ACCESSORIES:

- 19106513 Epoxi grid 497x510 for UP-451 professional cabinets. 3ud.
- 19106514 Epoxi grid 497x380 for UP-451 professional cabinets. 1ud.

DIMENSIONS



X Width	626 mm	X Gross width	666 mm
Y Depth	740 mm	Y Gross depth	780 mm
Z Height	1865 mm	Z Gross height	2010 mm
Net Weight	74,0 kg	Gross Weight	85,0 kg
Net Volume	0,864 M3	Gross Volume	1,040 M3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	0,186 KW
Voltage	230V - 1N
Phases	1N
Electric frequency	50Hz
Amperage (A)	1.3A

COLD TECHNICAL SPECIFICATIONS

Energy Efficiency Index	68,760 %
Temperature	0 +8 °C
Climate class	4
Refrigeration power	0,292 KW
Gas type	R-600a
GWP	3,000
Cooling gas load	0,082 KG
Gross internal volume	459,000 L
Noise level	43,000 DB
Condensation system	Static
Model Type	Vertical cabinet
Annual elec. consumption	866,000 KWH
Power consumption 24h	2,370 KWH
Refrigeration net.vol	395,000 L
Frozen net.vol	0 L
IEE	69,000
Clasif. Energy efficiency	D

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5+T - 6 A
Single-phase 230V wiring	2X1,5+T - 6 A



Catalogue
FOOD SERVICE

FMV

Chapter
REFRIGERATION

Zone:

Specific Model
UP-451 SS 230V 1N 50HZ

Item:

19089730

07/11/2025

The photo may show the standard model and not the configured one





Catalogue
FOOD SERVICE

FMV

Chapter
REFRIGERATION

Zone:

Specific Model
UP-451 SS 230V 1N 50HZ

Item:

19089730

07/11/2025

The photo may show the standard model and not the configured one

